

SEA

Stationary, Electric-Powered, Cold Water Pressure Washer

COLD WATER

ELECTRIC

STATIONARY



- Up to 4.2 GPM
- Up to 3000 PSI
- Stainless Steel or Mild Steel Cabinet
- Accepts Hot Water Up to 145°F



SEA3-11024D
Shown with stainless steel cabinet

SEA3-11024D
Shown with mild steel cabinet



- **Industrial-Grade Motor** is connected to the rugged, class-leading, tri-plunger, oil-bath **LT** (stainless steel model) or **LM** (mild steel model) **High-Pressure Pump** (with 7-year warranty) by dual, V-cogged belts. **Pulleys** are made of cast iron and can be easily adjusted by turning two bolts.
- Quick-couple **Nozzles** are made of hardened stainless steel and color-coded for easy selection of spray pattern: 15°, 25°, 40°.
- Heavy-duty **Cabinet** rides on four **Rubber Feet** for absorption of vibration.
- **Hour Meter** is standard on the Mild Steel versions only.
- **Inlet Filter** strainer protects pump from debris.
- Easily handles **Water Up To 145°**.
- 50 ft. of double steel-wire braid **High Pressure Hose** with 24-inch **Hose Guard** for burst protection and swivel crimp fitting for tangle-free handling of hose and trigger gun.
- Optional **Hose Reel** (#8.903-521.0) provides tangle-free handling of up to 100 ft. of high-pressure hose.
- Easy-to-attach **Detergent Injector** for easy application of soap.
- Helpful **Tri-Lingual Labels** with operating instructions in English, Spanish and French for added liability protection and operator convenience.
- **Compact Design**, 31" L x 21" W x 16" H.
- Many **Safety Features**, including a thermal pump protector to prevent the buildup of excessive pressures or heat.
- **Time-Delay Shutdown** (stainless steel model only) automatically turns off unit, if not in use for a set time, for protection against unattended operation.
- With the switch in the 'ON' position, the optional **Auto Start/Stop** function allows the unit to be turned on with the pull of the trigger for convenient remote operation. (This option replaces Time-Delay Shutdown.)
- Optional rust-free **Float Tank** with stainless steel inlet filter and backflow protection (stainless steel model only).

LANDA®

#LANDATOUGH
Pressure Washers Built to Last - landa.com

WHY CHOOSE THE SEA?

This top-of-the-line stationary cold-water series features a heavy-duty stainless steel or mild steel cabinet and comes standard with an insulated variable pressure wand, 50' of hose, and time delay shutdown. Available options include our LanCom wireless remote control, floor stand, and wall mount bracket assembly. This unit is ideal for cleaning a variety of indoor surfaces, and can be plumbed for plug-and-wash outdoor applications as well.



Model #	Part #	Cabinet	GPM	PSI	Pump RPM	Pump	Motor HP	Volts	Phase	Amps	Ship Wt (lbs)
SEA3-11024D	1.106-500.0	Stainless Steel	2.8	1000	1540	LB3030R	2.0	120	1	20	210
SEA4-20024A	1.106-501.0	Stainless Steel	4.2	2000	1013	LT6036R.2	6.2	230	1	28	280
SEA4-20024B	1.106-502.0	Stainless Steel	4.2	2000	1013	LT6036R.2	6.2	230	3	16	220
SEA4-20024C	1.106-503.0	Stainless Steel	4.2	2000	1013	LT6036R.2	6.2	460	3	7.2	220
SEA4-20024G	1.106-505.0	Stainless Steel	4.2	2000	997	LT6036R.2	6.2	208	1	30	297
SEA4-20024H	1.106-506.0	Stainless Steel	4.2	2000	1028	LT6036R.2	6.2	208	3	18.5	220
SEA4-30024B	1.106-507.0	Stainless Steel	3.5	3000	943	LT6036R.2	7.5	230	3	21.5	235
SEA4-30024C	1.106-508.0	Stainless Steel	3.5	3000	943	LT6036R.2	7.5	460	3	10.5	305
SEA3-11024D	1.106-583.0	Mild Steel	2.8	1000	1500	LB3030R	2.0	120	1	20	275
SEA4-20024A	1.106-584.0	Mild Steel	4.2	2000	1281	LM4035R.3	6.2	230	1	29	275
SEA4-20024B	1.106-585.0	Mild Steel	4.2	2000	1281	LM4035R.3	6.2	230	3	11	275
SEA4-20024C	1.106-586.0	Mild Steel	4.2	2000	1281	LM4035R.3	6.2	460	3	11	275
SEA4-20024H	1.106-587.0	Mild Steel	4.2	2000	1281	LM4035R.3	6.2	208	3	16	275
SEA4-30024B	1.106-588.0	Mild Steel	3.5	3000	1070	LM4035R.3	7.5	230	3	19	275
SEA4-30024C	1.106-589.0	Mild Steel	3.5	3000	1070	LM4035R.3	7.5	460	3	11	275

Dimensions: 31"L x 21"W x 16"H

Field Installed Options & Accessories

- 9.801-036.0 Cox Hose Reel Kit (floor stand / wall mount)
- 9.903-521.0 E-Zee Hose Reel & Mounting Kit
- 9.802-265.0 Hose Reel, Mini, (fits wall bracket, 150' capacity)
- 9.711-860.0 Hose Reel, Mini, (fits wall bracket, 100' capacity)
- 9.903-040.0 24" Floor Stand
- 9.801-034.0 36" Floor Stand
- 9.903-617.0 36" Floor Stand (stainless steel)

Mild Steel Models Only

- 9.803-045.0 Time Delay Shutdown Kit 120v 1ph •
- 9.929-374.0 Time Delay Shutdown Kit 208/230v 1ph •
- 9.903-041.0 Time Delay Shutdown Kit 3ph •
- 9.929-376.0 Auto start/Stop Kit 120v 1ph •
- 9.929-377.0 Auto Start/Stop Kit 208/230v 1ph •
- 9.903-047.0 Auto Start/Stop Kit 3ph •
- 9.801-033.0 Wall Mount Bracket Assembly

Stainless Steel Models Only

- 9.929-497.0 LanCom Kit 1-step 460V 3 ph •••
- 9.929-498.0 LanCom Kit 2-step 460V 3 ph •••
- 9.930-163.0 LanCom Kit 1-step 208/230V 3ph •••
- 9.930-177.0 LanCom Kit 2 step 208/230V 3ph •••
- 9.929-382.0 LanCom Kit 1-step 208/230v 1 ph •••
- 9.929-383.0 LanCom Kit 2-step 208/230v 1ph •••
- 9.903-461.0 Remote On/Off Switch Option ••
- 9.930-358.0 Additional LanCom Remote
- 9.903-619.0 Wall Mount Bracket Assembly
- 9.930-131.0 Wall Mount Bracket for Fixed LanCom Remote
- 9.903-511.0 Auto Start/Stop Kit 208/230/460v 3ph ••
- 9.929-380.0 Auto Start/Stop Kit 120v 1ph ••
- 9.929-381.0 Auto Start/Stop Kit 208/230 1ph ••
- 9.903-448.0 Float Tank Option with Inlet Soap Injection ••

- Factory Installed
- Not compatible with LanCom
- Not compatible with Auto Start/Stop or Float Tank options
- Not available on stainless steel model SEA3-11024D

DETERGENT FOR EVERY JOB

Landa innovative detergent lineup makes your cleaning job easier and faster. Phosphate-free to meet the most stringent environmental demands without sacrificing cleaning effectiveness. We'll match you with a product designed for your specific application.



LANDA®

Your Authorized Landa Dealer:



633 N Helena St • Spokane WA 99202
(509) 535-1555 | info@northstardirect.com

NORTHSTARDIRECT.COM