

## **HWE SERIES** ALL-ELECTRIC

## **FEATURES**

3.5 to 4.0 GPM @ 2000 to 3000 PSI **Auto Start/Stop** 

> **Magnetic Motor** Starter for long life of reliable starting.

> Mounted on a Power Platform with four vibration isolators to minimize shaking and stress on the frame.

The **Auto Start** function allows the unit to be turned on with the pull of the trigger for convenient remote operation.

Inlet Filter strainer protects pump from debris.

..........



50 ft. High Pressure Hose rated for up to 5000 PSI with Insulated, fatigue-free Trigger Gun and stainless steel, duallance Variable Pressure Wand.

Three quick-coupler **Nozzles** are made of hardened stainless steel and mounted for ready access.

**PRESSURE WASHERS / SINCE 1970** 

**HOT WATER** 

ALL-ELECTRIC

**BELT DRIVE** 

Heavy-duty Upper and Lower Cabinet is protected by an epoxy powder coat

Safety Low-Water Float Switch protects heating elements from burn out due to lack of water.

Easy-to-attach Detergent Injector for easy soap application.

..........

Contains nine high-efficiency Heating Elements that do not come in contact with the pressurized water, resulting in reduced scale build up, lower maintenance, and longer life.

Hotsy-designed Triplex Pumps carry a 7-year limited warranty and Heater Coil carries a 5-year warranty.







## **OPTIONS FOR HWE SERIES**

Stainless Steel Washer Wrap Option, Time Delay Shut Down



California Air Resources **Board** Verified

MODEL	PART NO.	GPM	PSI	HP	MOTOR	AMPS	VOLT/PH	Kva Hour	PUMP MODEL	PORTABILITY	DIM (LXWXH)	SHIP WT (LBS)
HWE-402009C	1.109-646.0	4.0	2000	6.2	Baldor	55	460/3	40.5	138,308	HM4030R.3	34"x25"x52"	620
HWE-403009C	1.109-647.0	3.5	3000	7.5	WEG	59	460/3	40.5	138,308	HM4030R.3	34"x25"x52"	640
HWE-402009F	1.109-958.0	3.5	2000	5	Baldor	46	575/3	40.5	138,308	HM4030R.3	34"x25"x52"	620
HWE-403009F	1.109-959.0	3.5	3000	7.5	Baldor	49	575/3	40.5	138,308	HM4030R.3	34"x25"x52"	640

The Pressure Washer The Pros Use.

**EST. 1970** 

**NOTE:** We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at + 10% and in some cases are tighter within +\_ 5% of listed specifications.

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

## HOTSY.COM

Tel: 800.525.1976 Fax: 888.880.9631 Email: info@hotsy.com

**VISIT US ONLINE** 

Facebook/Instagram HotsyCleaningSystems

LinkedIn Hotsy-Corp

Twitter TheHotsyMan

YouTube HotsyCleaningSystems

Get Hotsy Email Bit.ly/GetHotsy

© 2021 Kärcher North America P/N HOT\_HWE Effective 06/21

Distributed by:



1210 N Oregon Ave, Pasco, WA 99301 northstarhotsy.com | info@northstarhotsy.com (509) 547-2323