ELECTRIC

Compact Natural Gas-Heated Hot Water

Pressure Washer

- Up to 5.0 GPM / 3,000 PSI
- Belt-Drive Pump
- Compact Stationary Design
- Natural Gas or LP Heated





Control panel with hour meters for burner and pump



Easy access to all internal



Drop-in hose reel (optional)











- High-efficiency burner has electronic ignition standard on all models, eliminating the hassle of constantly lighting the pilot flame.
- Industrial-duty totally enclosed fan-cooled (TEFC) electric motor with multiple voltage options and thermal overload protection.
- Extra-durable stainless-wrapped heating coil made of leak-free, cold-rolled, Schedule 80 steel pipe with 5-year warranty.
- Rugged steel frame with laser-cut branding and black powder-coat finish for all-weather protection (stainless steel option also available).
- Removable panels with quick-release latches for easy servicing and bulb seals to absorb vibration during use.
- Large electrical box with knockouts for additional wiring.

- Industrial-grade, dual belt-driven high-pressure pump has a tri-plex, forged brass head with a 7-year limited warranty and U-seals for greater pump protection. Cast-iron, bushed-bore pulleys with two-bolt adjustment offer long life and easy maintenance.
- Control panel features overload-protected control switches including chemical control operation and interdependent dual hour meters to measure motor and burner runtime.
- Brass anti-syphon detergent metering valve locks out air and dispenses precise amount of cleaning agent.
- Pressure relief valve prevents buildup of excessive pressure or heat.
- Three quick-couple hardened stainless steel nozzles mounted for ready access.

- Top-of-the-line Tuff-Skin hose offers seven times the abrasion resistance of other high-pressure hoses, 24-inch hose guard for burst protection, and swivel swedge fitting for twist-free operation.
- Optional heavy-duty hose reel with easy drop-in installation.
- Insulated fatigue-free trigger gun and chromeplated dual lance variable pressure wand offer easy cleaning and pressure adjustment while washing.
- Programmable smart control provides complete control of runtime and allows addition of auto start/stop and time delay shutdown options without changing any hardware.
- Tri-lingual labels with operating instructions in English, Spanish and French for operator safety.



VHG

WHY CHOOSE THE VHG?

Redesigned with a tougher look and streamlined serviceability, the upgraded VHG offers the same compact, heavy duty cleaning power of its decades-old predecessor. This natural gas model's smaller footprint makes it an ideal choice for congested work areas or wash bays where space is at a premium. The VHG's compact size does not compromise its efficiency; delivering pressure of up to 3000 PSI at 5.0 GPM, this machine supplies enough cleaning power to tackle a variety of demanding jobs.



Model #	Part#	Heat	GPM	PSI	Pump RPM	Pump	Motor HP	Volts	Phase	Amps	Approx BTUs	Ship Wt (lbs)
VHG4-2200	1.109-223.0	NG	4.0	2200	1037	LT6036R	6.2	208	1	29	390,000	736
VHG4-2200	1.109-224.0	LP	4.0	2200	1037	LT6036R	6.2	208	1	29	378,617	736
VHG4-2200	1.109-225.0	NG	4.0	2200	1037	LT6036R	6.2	208	3	18	390,000	703
VHG4-2200	1.109-226.0	LP	4.0	2200	1037	LT6036R	6.2	208	3	18	378,617	703
VHG4-2200	1.109-227.0	NG	4.0	2200	1037	LT6036R	6.2	230	1	27	390,000	730
VHG4-2200	1.109-228.0	LP	4.0	2200	1037	LT6036R	6.2	230	1	27	378,617	730
VHG4-2200	1.109-229.0	NG	4.0	2200	1031	LT6036R	6.2	230	3	16	390,000	703
VHG4-2200	1.109-230.0	LP	4.0	2200	1031	LT6036R	6.2	230	3	16	378,617	703
VHG4-2200	1.109-231.0	NG	4.0	2200	1031	LT6036R	6.2	460	3	7	390,000	703
VHG4-2200	1.109-232.0	LP	4.0	2200	1031	LT6036R	6.2	460	3	7	378,617	703
VHG4-3000	1.109-233.0	NG	4.0	3000	1011	LT6036R	8.2	208	1	38	390,000	740
VHG4-3000	1.109-234.0	LP	4.0	3000	1011	LT6036R	8.2	208	1	38	378,617	740
VHG4-3000	1.109-235.0	NG	4.0	3000	1011	LT6036R	8.2	208	3	27	390,000	735
VHG4-3000	1.109-236.0	LP	4.0	3000	1011	LT6036R	8.2	208	3	27	378,617	735
VHG4-3000	1.109-237.0	NG	4.0	3000	994	LT6036R	8.2	230	1	36	390,000	759
VHG4-3000	1.109-238.0	LP	4.0	3000	994	LT6036R	8.2	230	1	36	378,617	759
VHG4-3000	1.109-239.0	NG	4.0	3000	1011	LT6036R	8.2	230	3	25	390,000	735
VHG4-3000	1.109-240.0	LP	4.0	3000	1011	LT6036R	8.2	230	3	25	378,617	735
VHG4-3000	1.109-241.0	NG	4.0	3000	1011	LT6036R	8.2	460	3	15	390,000	735
VHG4-3000	1.109-242.0	LP	4.0	3000	1011	LT6036R	8.2	460	3	15	378,617	735
VHG5-3000	1.109-243.0	NG	5.0	3000	1224	LT6036R	10	208	3	33	390,000	743
VHG5-3000	1.109-244.0	LP	5.0	3000	1224	LT6036R	10	208	3	33	378,617	743
VHG5-3000	1.109-245.0	NG	5.0	3000	1224	LT6036R	10	230	3	29	390,000	744
VHG5-3000	1.109-246.0	LP	5.0	3000	1224	LT6036R	10	230	3	29	378,617	744
VHG5-3000	1.109-247.0	NG	5.0	3000	1224	LT6036R	10	460	3	14	390,000	744
VHG5-3000	1.109-248.0	LP	5.0	3000	1224	LT6036R	10	460	3	14	378,617	744

Dimensions: 20.6" L x 51.875" W x 51.46" H

Field Installed Options & Accessories

8.924-815.0	Remote, kit, operator station
8.924-814.0	Kit, wireless, 1 receiver, 1 remote
8.925-072.0	Kit, wireless, 1 receiver, 2 remote
8.924-878.0	Kit, wall mount, wireless remote
9.802-633.0	Regulator, L.P. assembly
8.933-404.0	Accessory kit water inlet
8.933-405.0	Accessory kit drip pan
8.933-406.0	Accessory kit 100' hose reel
8.717-728.0	Draft Diverter, 8", 24 gauge galv
8.933-320.0	Accessory kit float tank lid
8.933-416.0	Machine Stand stationary

THE RIGHT TOOLS FOR ANY JOB

Landa's innovative detergent and accessory lineup makes your cleaning job easier and faster. We'll match you with the best tools for your specific application.





