

Stainless steel cold-water cabinet that accepts pre-heated water.



HD CABINET - BELT DRIVE



Industrial throughout.

Our cold-water cabinet units really take the heat, accepting pre-heated water up to 145°F. Protected in durable stainless steel cabinets, they demonstrate industrial strength throughout, including belt-drive Kärcher crankcase pumps, industrial motors, and magnetic starters for operator safety.















1 Safety features and optional wheel kit with detergent rack

- A thermal pump protector to prevent the buildup of excessive pressures or heat.
- Time-Delay Shutdown automatically turns off unit, if not in use for a set time, for protection against unattended operation
- High-Pressure Pump (with 7-year warranty) by dual, V-cogged belts.
- Pulleys are made of cast iron and can be easily adjusted by turning two bolts
- Take the HD Cabinet mobile with the optional stainless steel wheel kit with detergent rack.

2 Floor stand

 $\hfill \blacksquare$ Mount to floor stand to centralize cleaning

3 EASY!Force trigger gun

 EASY!Force trigger gun with cruise control like technology uses its own recoil force to hold the trigger down – so, no more sore hands after hours of use.

Technical data and equipment.

TECHNICAL DATA										
Model	Part No.	GPM	PSI	Drive	НР	Electrical	Amps	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) Inches
HD 2.8/10 ST Ed B	1.106-603.0	2.8	1000	Belt	2	120V / 1ph	20	Kärcher KM	210	31 x 21 x 16
HD 3.9/20 ST Ea B	1.106-604.0	3.9	2000	Belt	6	230V / 1ph	29	Kärcher KM	285	31 x 21 x 16
HD 3.9/20 ST Ec B	1.106-605.0	3.9	2000	Belt	6	460V / 3ph	11	Kärcher KM	260	31 x 21 x 16
HD 3.9/20 ST Eh B	1.106-606.0	3.9	2000	Belt	6	208V / 3ph	16	Kärcher KM	265	31 x 21 x 16
HD 3.5/30 ST Ea B	1.106-607.0	3.5	3000	Belt	7.5	230V / 1ph	36	Kärcher KM	330	31 x 21 x 16
HD 3.5/30 ST Ec B	1.106-608.0	3.5	3000	Belt	7.5	460V / 3ph	11	Kärcher KM	270	31 x 21 x 16
HD 5.6/25 ST Ec B	1.106-609.0	5.6	2500	Belt	10	460V / 3ph	13.5	Kärcher KX	310	31 x 21 x 16

ACCESSORIES

Order No.	Description
8.756-481.0 ■	EASY!Force trigger gun (North American Model) - zero force required. Standard 1/4" connection for wand, 3/8" connection for hose.
9.801-013.0	Hour Meter (factory included)

OPTIONS (FACTORY INSTALLED)

Order No.	Description
8.903-045.0	Kit Time Delay Shutdown (for HD 2.8/10 ST Ed B model)
8.929-374.0	Kit Time Delay Shutdown (for HD 4.2/20 ST Ea B model)
8.903-041.0	Kit Time Delay Shutdown (for HD 3.5/30 and HD 4.2/20 models, excluding HD 4.2/20 ST Ea B)
8.929-376.0	Kit Auto Start/Stop (for HD 2.8/10 ST Ed B model)
8.929-377.0	Kit Auto Start/Stop (for HD 4.2/20 ST Ea B model)
8.903-047.0	Kit Auto Start/Stop (for HD 3.5/30 and HD 4.2/20 models, excluding HD 4.2/20 ST Ea B)

OPTIONS (FIELD INSTALLED)

Order No.	Description			
9.801-033.0	Wall Mount Kit			
8.903-043.0	Stainless Steel Wall Mount Kit			
8.903-040.0	Floor Stand, 24" short			
9.801-034.0	Floor Stand, 36" Tall			
8.903-617.0	Stainless Steel Floor Stand, 36" Tall			
8.941-546.0	Stainless Steel Floor Stand, without Hose Hanger			
9.801-036.0	Hose Reel Kit, Floor Stand Only, 100 ft, No Hose			
9.801-035.0	Wheel Kit for Floor Stands (4 casters)			
9.801-031.0	Wheel Kit with Detergent Rack			
8.904-527.0	Wheel Kit with Detergent Rack (stainless steel)			
8.750-682.0	100' x 3/8" fixed base hose reel			
8.919-437.0	Wall Mount			
8.903-039.0	Kit, Hose Reel w/Bracket for Stand, Wall Mount Kits			

[■] Included □ Optional ■ Not compatible with EASY!Lock

Please contact us for more information:

Kärcher U.S.A.

6398 N. Kärcher Way Aurora, CO 80019

Tel. 888-805-9852 Fax 800-248-8409











KarcherUSA



633 N Helena St. Spokane, WA 99202 (509) 535-1555 | info@northstardirect.com

1210 N Oregon Ave. Pasco, WA 99301 (509) 547-2323 | info@northstarhotsy.com