

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 7/6/2021 Version: 1.0

: Mixture : 1934LAN
ISE
Cleansing product
 800-535-5053 For Chemical Emergency Call INFOTRAC 24hr/day 7days/week Within USA and Canada: 1-800-535-5053 Outside USA and Canada: 1-352-323-3500 (collect calls accepted)
re
H314Causes severe skin burns and eye damageH318Causes serious eye damage
onary statements
 Danger H314 - Causes severe skin burns and eye damage H318 - Causes serious eye damage
 P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearams and face thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P310 - Immediately call a poison center/doctor	
P363 - Wash contaminated clothing before reuse.	
P405 - Store locked up.	
P501 - Dispose of contents/container to hazardous or special waste collection	on point, in
accordance with local regulations	

2.3. Other hazards which do not result in classification Other hazards which do not result in classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
SODIUM HYDROXIDE	CAS-No.: 1310-73-2	10 – 20
DIPROPIONATE AMPHOTERIC	CAS-No.: 64972-19-6	1.35 – 2.25
SODIUM XYLENE SULFONATE	CAS-No.: 1300-72-7	1 – 5
BUTHOXYETHANOL	CAS-No.: 111-76-2	1 – 5

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.
4.2. Most important symptoms and e	ffects (acute and delayed)
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measu	ires	
5.1. Suitable (and unsuitable) extin	guishing media	
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.	

EN (English US)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Specific hazards arising from the cher	nical
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 No fire hazard. No direct explosion hazard. Toxic fumes may be released.
5.3. Special protective equipment and pred	cautions for fire-fighters
Firefighting instructions Protection during firefighting	 Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
SECTION 6: Accidental release measu	res
6.1. Personal precautions, protective equip	pment and emergency procedures
General measures	: Do not handle until all safety precautions have been read and understood.
6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for co	ontainment and cleaning up
For containment Methods for cleaning up Other information	 Absorb spilled material with sand or earth. Take up liquid spill into absorbent material. Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed Precautions for safe handling	 Not expected to present a significant hazard under anticipated conditions of normal use. Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, including a	any incompatibilities
Technical measures Storage conditions	Comply with applicable regulations.Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

FLEET INTERIOR TANK CLEANER	
No additional information available	
DIPROPIONATE AMPHOTERIC (64972-19-6)	
No additional information available	
SODIUM XYLENE SULFONATE (1300-72-7)	
No additional information available	
SODIUM HYDROXIDE (1310-73-2)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL Ceiling	2 mg/m ³
BUTHOXYETHANOL (111-76-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE)
ACGIH OEL TWA [ppm]	20 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2019
USA - OSHA - Occupational Exposure Limits	
Local name	2-Butoxyethanol
OSHA PEL (TWA) [1]	240 mg/m ³
OSHA PEL (TWA) [2]	50 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
8.2. Appropriate engineering controls	
Appropriate engineering controls :	Ensure good ventilation of the work station.
Environmental exposure controls :	Avoid release to the environment.
8.3. Individual protection measures/Personal	protective equipment
Hand protection:	
Protective gloves	
Eye protection:	
Safety glasses	
Skin and body protection:	
Wear suitable protective clothing	
Respiratory protection:	
In case of insufficient ventilation, wear suitable respirat	ory equipment

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

: Liquid
: Liquid.
: amber
: characteristic
: No data available
: No data available
: 13.6
: Not applicable
: No data available
: Not applicable.
: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5.	Incom	patible	materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11.1. Information on toxicological effe	ots
Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
SODIUM XYLENE SULFONATE (1300-	
LD50 oral rat	> 7000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Read-across, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Read-across, Dermal, 14 day(s))
BUTHOXYETHANOL (111-76-2)	
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LC50 inhalation rat (mg/l)	> 4.26 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1414 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
Skin corrosion/irritation	Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
BUTHOXYETHANOL (111-76-2)	
IARC group	3 - Not classifiable
Reproductive toxicity	Not classified
STOT-single exposure	: Not classified
BUTHOXYETHANOL (111-76-2)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	Not classified
BUTHOXYETHANOL (111-76-2)	
NOAEL (dermal,rat/rabbit,90 days)	> 150 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Derma Toxicity: 90-Day Study)
Aspiration hazard	Not classified
/iscosity, kinematic	: No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after eye contact
Symptoms/effects after ingestion

: Serious damage to eyes.: Burns.

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general :	Before neutralisation, the product may represent a danger to aquatic organisms.
SODIUM XYLENE SULFONATE (1300-72-7)	
LC50 - Fish [1]	> 1000 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)
EC50 - Daphnia [1]	> 1000 mg/l (EPA OTS 797.1300, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
SODIUM HYDROXIDE (1310-73-2)	
LC50 - Fish [1]	45.4 mg/l (96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Solution >=50%)
EC50 - Daphnia [1]	40.4 mg/l (48 h, Ceriodaphnia sp., Experimental value, Nominal concentration)
BUTHOXYETHANOL (111-76-2)	
LC50 - Fish [1]	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)
EC50 - Daphnia [1]	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	1840 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '21 d'

12.2. Persistence and degradability

SODIUM XYLENE SULFONATE (1300-72-7)		
Persistence and degradability	Readily biodegradable in water.	
SODIUM HYDROXIDE (1310-73-2)		
Persistence and degradability	Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable (inorganic)	
ThOD	Not applicable (inorganic)	
BUTHOXYETHANOL (111-76-2)		
Persistence and degradability	Readily biodegradable in water.	

12.3. Bioaccumulative potential

SODIUM XYLENE SULFONATE (1300-72-7)	
Partition coefficient n-octanol/water (Log Pow)	-3.12 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Bioaccumulative potential	Not bioaccumulative.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SODIUM HYDROXIDE (1310-73-2)		
Bioaccumulative potential	Not bioaccumulative.	
BUTHOXYETHANOL (111-76-2)		
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value, BASF test, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	

12.4. Mobility in soil

SODIUM XYLENE SULFONATE (1300-72-7)		
Surface tension	71 mN/m (20 °C, 90 %, EU Method A.5: Surface tension)	
Ecology - soil	No (test)data on mobility of the substance available.	
SODIUM HYDROXIDE (1310-73-2)		
Ecology - soil	No (test)data on mobility of the substance available.	
BUTHOXYETHANOL (111-76-2)		
Surface tension	65.03 mN/m (20 °C, 2 g/l)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.451 – 0.882 (log Koc, SRC PCKOCWIN v2.0, Calculated value)	
Ecology - soil	Highly mobile in soil.	

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations	
13.1. Disposal methods	
Regional legislation (waste) Waste treatment methods	 Disposal must be done according to official regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information	
14.1. UN number	
DOT NA No	: UN1760
14.2. UN proper shipping name	
Proper Shipping Name (DOT)	: Corrosive liquids, n.o.s. (SODIUM HYDROXIDE), 8, II

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.3. Transport hazard class(es)	
DOT Transport hazard class(es) (DOT) Hazard labels (DOT)	: 8 : 8 (CORROSIVE 8
14.4. Packing group	
Packing group (DOT)	: 11
14.5. Environmental hazards	
Other information	: No supplementary information available.
14.6. Special precautions for user	
DOT UN-No.(DOT)	: UN1760
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

SODIUM HYDROXIDE (1310-73-2)	
CERCLA RQ	1000 lb
15.2. International regulations	

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases		
H314	Causes severe skin burns and eye damage	
H318	Causes serious eye damage	
NFPA health hazarc	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.	
NFPA fire hazard	: 1 - Materials that must be preheated before ignition can occur.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA reactivity	 0 - Material that in themselves are normally stable, even under fire conditions.
Hazard Rating Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
Personal protection	: C - Safety glasses, Gloves, Synthetic apron
Safety Data Sheet (SDS), USA	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.